

# DATASHEET

## QuickFix Detectable

### 1. Identification of the substances/preparation and of the company/undertaking

Date issued	06.04.2006
Revision	06.04.2006
Product name	Quick Fix Detectable
Index no.	Version 1.0
Use of the substance/preparation	Plaster QuickFix Detectable

#### Producer

Company name	Plum A/S
Postal address	Frederik Plums Vej 2
Postcode	5610
Place name	Assens
Country	Danmark
Tel.	0045 6471 2112
Fax	0045 6471 21 25
E-mail	<a href="mailto:info@plum.dk">info@plum.dk</a>
Website	<a href="http://www.plum.dk">http://www.plum.dk</a>

### 2. Backing

Composition	Polyethylene film
Colour	Blue
Weight (g/m <sup>2</sup> )	62-69
Thickness (µm <sup>2</sup> )	70

### 3. Adhesive

Composition	Hypoallergenic acrylic polymer
Weight (g/m <sup>2</sup> )	28-36

### 4. Coated backing

Weight (g/m <sup>2</sup> )	90-105
Adhesion to steel by peeling at 180° (N/cm)	>1,6
M.V.T.R. (g/m <sup>2</sup> /24h/37°C)	<500 (non perforated)
Water resistant	yes

### 5. Absorbent pad

Total weight (g/m <sup>2</sup> )	220-280
Absorbency (g/100 cm <sup>2</sup> )	5-10
"Detectable layer"	Aluminium foil facing the backing
Absorbent layer	Viscose, polypropylene/polyethylene nonwoven
Colour	White
Antiadherent layer	Microperforated PE film

### 6. Liner

#### Monosiliconated paper

Weight (g/m <sup>2</sup> )	57-63
----------------------------	-------

QuickFix Detectable

Colour White

## 7. Primary packing

### Individual pouch: paper + clear film

Paper composition	Cold sealed paper
Paper weight (g/m <sup>2</sup> )	40-50
Film composition	Polyethylene terephthalate / polyethylene
Film weight (g/m <sup>2</sup> )	52-67