

Date: 17-March-2013

Reference: 8352-8900-7-1, 230V Compressor with Nebulizer

Data Sheet

8352 Compressor Part Description*	Material
Plastic Case	Molded ABS
Fitting, Exhaust	Molded, Nylon
Stem bumper (foot)	Rubber
Air filter	Open cell foam
Rocker switch	Plastic

Temperature: Operation: 10°C to 40°C/ 50°F to 104°F Storage: -15°C to 50°C / 5°F to 122°F Transport: -15°C to 70°C/ 5°F to 158°F	Humidity: Operation: 10% to 90%RH non-condensing Storage: 10% to 90%RH non-condensing Transport: 10% to 90% RH non-condensing
Operating conditions: Atmospheric pressure: Operation: 700-1060 hPa	Performance Characteristics: Air Flow: 8 LPM free flow 5.5 LPM through a Salter Nebulizer Pressure: ≥ 30 PSI Maximum

8900 Nebulizer Part Description	Material
Cup, Nebulizer	Polystyrene
Top, Nebulizer	Polypropylene
Insert, Nebulizer	Polystyrene
Tubing, Aerosol 6"	Ethylene Vinyl Acetate Copolymer
T, Anti-drool	K-resin
Mouthpiece (Bagged)	High Density Polyethylene
Tubing, 3-channel, 7 ft.	Polyvinylchloride
Connector, End Piece	Polyvinylchloride



Salter Labs manufactures product from medical grade materials in compliance with Good Manufacturing Practices (GMP's) as listed in 21 C.F.R. (U.S. code of Federal Regulations)

I certify that the above information is accurate to the best of my abilities.

Please do not hesitate to contact me if I can be of any further assistance. My email address is mcollins@salterlabs.com and my phone number is 760-795-7102.

A handwritten signature in black ink that reads 'Peggy Collins'.

Peggy Collins
Regulatory Affairs
Salter Labs.