

1220, 1225 Swivel Connector

LATEX FREE | SINGLE PATIENT USE | DISPOSABLE

Device Manufacturing Specifications

Reference Number	1220, 1225
Manufacturer	SunMed LLC/Salter Labs
Classification – US	BYX
FDA Product Code	Class I
Classification – EU	Class IIa
CE Mark/Notified Body	CE 2797/BSI Group
EU Authorized Representative	MT Promedt Consulting Group GmbH
Classification – Canada	Class II
EMDN Code	R03010204 - Oxygen Administration Tubing
GMDN Code	12875, Oxygen Administration Tubing
UMDNS Code	12875, Tubing, Oxygen Connecting
Made In	Mexico
Usage	Disposable, Single Patient Multiple Use
Sterile	No
Patient Population	Infant, Pediatric, Adult
Packaging	25, or 100/Case
Shelf Life	5 Years

Description: The 2-piece swivel connector has a 360 degrees rotation. The Swivel connector is available with two tapered male end connectors or with a male tapered end and female trumpet connector.

Intended Purpose: Intended to join two lengths of oxygen supply tubing.

Area of Use: Hospitals, sub-acute, medical clinics, pre-hospital, home, surgical centers, skilled nursing facilities.

Contraindications: No known.

Device Specifications

Description	Specification
Low Pressure	≤ 10 PSI (689 mbar)
Flow Rate	≤ 15 LPM
Length	2" (0.05 m)
Tubing End Connector (1220)	Tapered Male to Male
Tubing End Connector (1225)	Tapered Male to Female Trumpet
Tubing Compatibility	O ₂ Tubing with 5 mm to 7 mm End Connectors
Operating Temperature	5°C to 40°C
Storage Temperature	-20°C to 50°C

Device Material

Component	Material
Body	High Density Polyethylene (HDPE), White
O-Ring	Silicone
Female Tubing Connector (1225)	Polycynyl Chloride (PVC)

Latex: Salter Labs® does not utilize latex or latex-containing material to manufacture products. To the best of our knowledge latex do not meet components or finished good during the manufacturing process.

Phthalates: The selected materials are Non-DEHP; DEHP was not intentionally added as part of the manufacturing process.

BPA: Salter Labs does not intentionally add or use material with bisphenol A (BPA) to manufacture bubble humidifiers.

Mercury-Lead: The selected materials do not contain lead or mercury.

Biocompatible per device classification in ISO 10993.



1220



1225

Part Number	UOM	GTIN
1220-0	Each	00607411001130
1220-0-25	Case	20607411001134
1220-0-100	Case	30607411001131
1225-0	Each	00607411001215
1225-0-25	Case	20607411001219